



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SPIKECUBE

Surge Suppressor - State of the art protection for every application

Highlights

- 1 outlet/direct plug-in
- 750 joule rating



Description

The SPIKECUBE Surge Suppressor from Tripp Lite is a direct plug-in suppressor providing protection on one AC outlet. Its small size makes it ideal for protecting laptop computers, projectors and other portable electronics. A "Protected" LED illuminates to indicate that adequate surge suppression is available. The unit has 750 joules of surge energy absorption.

Applications

- Ideal for laptop computers, video projectors, office machines, and appliances

Package Includes

- SPIKECUBE Surge Suppressor
- Warranty and instruction information

Features

- 1 outlet; direct plug-in
- Surge energy absorption: 750 joules; 6,500 amps
- Lifetime product warranty

Specifications

OVERVIEW	
Intended Application	Home/Office, Travel
SYSTEM OVERVIEW	
Voltage compatibility	120 VAC
Frequency compatibility	50/60 Hz
OUTPUT	
Output volt amp capacity (amps)	15
Output watts	1800

Outlet quantity / type	1 NEMA 5-15R
INPUT	
Input connection type	NEMA 5-15P input plug
Input cord length (ft.)	Direct plug-in
Recommended Electrical Service	120V (110-125V)
LEDS ALARMS & SWITCHES	
Diagnostic LEDs	Built-in "Protected" status indicator
SURGE / NOISE SUPPRESSION	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC suppression joule rating	750 joules
Clamping voltage (RMS)	150V
AC suppression response time	< 1 ns
UL1499 let through rating	400V - UL Verified
DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection	No
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
PHYSICAL	
Material of construction	Plastic
Form factors supported	Direct plug in suppressor supports wall-mounting directly into AC receptacle
Style	Direct plug-in
SPECIAL FEATURES	
Appearance	Ultra-compact portable direct plug-in protector in an attractive, grey lightweight enclosure
CERTIFICATIONS	
UL1449 1998 Rev. (AC Suppression)	UL1449
Approvals	Exceeds IEEE 587 category A&B specifications
WARRANTY	
Product Warranty Period	Lifetime

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=120.